



Cases Ltd

**Peli 1120 case**  
**Peli protector cases - Crushproof peli case**



Black    Yellow    Orange

**Peli protector cases - Crushproof peli case - 1120 case SPECIFICATIONS**

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
20.6 x 16.7 x 9 cm (8" x 7" x 4")		18.4 x 12.1 x 7.8 cm (7" x 5" x 3")	
Lid Depth	Bottom Depth	Total Depth	
1.3 cm (1")	6.5 cm (2.56")	7.8 cm (3.06")	
Weight w/Foam	Weight w/o Foam	Buoyancy Max.	
0.56 kg. (1.23 lbs)	0.53kg (1.17 lbs.)	2.27 kg (5 lbs.)	
Range Temperature			
-40 / 99° C (-40 / 210° F)			

**1120 Case Certificates**

- IP67(1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

Interior dimensions:

18.4 x 12.1 x 7.8 cm (7" x 5" x 3")

**Watertight, crushproof, and dust proof**

- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Unconditionally Guaranteed

**Materials**

Body	Latch	Lid O-Ring	Pins
Polypropylene	Polypropylene	PolymerStainless Steel	
Foam	Purge Body	Purge Vent	Purge O-Ring
1.3 lb Polyurethane	ABS	3 Micron Hydrophobic Non-Woven PET	70 Shore Nitrile

**Configuration**

Cat. #	Description
1120	Peli protector cases - Crushproof peli case - 1120 case
1120NF	1120 Case (no foam)

**Peli protector cases - Crushproof peli case - 1120 case Accessories**

Cat. #	Description
1120PF	Special Application Panel Frame
1121	3 pc. Replacement Foam Set
1123	Replacement O-ring

3D Flight Cases Ltd

Phone: +44 (0) 1733 269026 • Fax: +44 (0) 1733 530535

website: [www.3D-FlightCase.co.uk](http://www.3D-FlightCase.co.uk)