



Cases Ltd

Peli 1150 Case
Peli protector cases - Protector case



Interior dimensions:

20.8 x 14.4 x 9.2 cm (8" x 6" x 4")

Watertight, crushproof, and dust proof

Open cell core with solid wall design - strong, light weight

O-ring seal

Automatic Pressure Equalization Valve

Stainless steel hardware

Pick 'N' Pluck™ with convoluted lid foam

Unconditionally Guaranteed



Peli protector cases - Protector case - 1150 case SPECIFICATIONS

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
23.2 x 19.2 x 11.1 cm (9" x 8" x 4")		20.8 x 14.4 x 9.2 cm (8" x 6" x 4")	
Lid Depth	Bottom Depth	Total Depth	
1.9 cm (1")	7.3 cm (2.87")	9.2 cm (3.62")	
Weight w/Foam	Weight w/o Foam	Buoyancy Max.	
0.9 kg. (1.98 lbs)	0.8kg (1.76 lbs.)	3.63 kg (8 lbs.)	
Range Temperature			
-40 / 99° C (-40 / 210° F)			

Materials

Body	Latch	Lid O-Ring	Pins
Polypropylene	Polypropylene	PolymerStainless Steel	
Foam	Purge Body	Purge Vent	Purge O-Ring
1.3 lb Polyurethane	ABS	3 Micron Hydrophobic Non-Woven PET	70 Shore Nitrile

Configuration

Cat. #	Description
1150	Peli protector cases - Protector case - 1150 case
1150NF	1150 Case (no foam)

Peli protector cases - Protector case - 1150 case Accessories

Cat. #	Description
1150PF	Special Application Panel Frame
1151	3 pc. Replacement Foam Set
1153	Replacement O-ring

1150 Case Certificates

- IP67(1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

3D Flight Cases Ltd
 Phone: +44 (0) 1733 269026 • Fax: +44 (0) 1733 530535
 website: www.3D-FlightCase.co.uk