



Cases Ltd

Peli 1300 case
Peli protector cases - Total protection box



Interior dimensions:

25.1 x 17.8 x 15.5 cm (10" x 7" x 6")

Watertight, crushproof, and dust proof

Easy-open, double-step latches

Open cell core with solid wall design - strong, light weight

O-ring seal

Automatic Pressure Equalization Valve

Stainless steel hardware

Pick 'N' Pluck™ with convoluted lid foam

Unconditionally Guaranteed



Peli protector cases - Total protection box - 1300 case SPECIFICATIONS

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
27 x 24.6 x 17.4 cm (11" x 10" x 7")		25.1 x 17.8 x 15.5 cm (10" x 7" x 6")	
Lid Depth	Bottom Depth	Total Depth	
3 cm (1")	12.5 cm (4.93")	15.5 cm (6.11")	
Weight w/Foam	Weight w/o Foam	Buoyancy Max.	
1.6 kg. (3.53 lbs)	1.4kg (3.09 lbs.)	5.6 kg (12.35 lbs.)	
Range Temperature			
-40 / 99° C (-40 / 210° F)			

Materials

Body	Latch	Lid O-Ring	Pins
Polypropylene	ABS	Polymer	Stainless Steel
Foam	Purge Body	Purge Vent	Purge O-Ring
1.3 lb Polyurethane	ABS	3 Micron Hydrophobic Non-Woven PET	70 Shore Nitrile

Configuration

Cat. #	Description
1300	Peli protector cases - Total protection box - 1300 case
1300NF	1300 Case (no foam)

Peli protector cases - Total protection box - 1300 case Accessories

Cat. #	Description
1200PF	Special Application Panel Frame
1400IP	Instapak Quick® RT
1301	4 pc. Replacement Foam Set
1203	Replacement O-ring

1300 Case Certificates

- IP67(1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

3D Flight Cases Ltd

Phone: +44 (0) 1733 269026 • Fax: +44 (0) 1733 530535

website: www.3D-FlightCase.co.uk