



Peli 1460EMS Case



Interior dimensions:

47.1 x 25.2 x 27.7 cm (19" x 10" x 11")

Specifically designed in conjunction with Fire department and EMS personnel

Lockable compartment for controlled substances

Adjustable tray dividers allow for easy customisation

Sharps storage bracket included

Top lid opens up to 180° for on-the-field anti-roll stability when open

O-ring seal for dust and water resistant seal (IP66)

Easy open Double Throw latches

Open cell core with solid wall design - strong, light weight

Automatic Pressure Equalisation Valve

Comfortable rubber over-moulded handles

Stainless steel hardware and padlock protectors


Personalised nameplate service available

Unconditional Guarantee of Excellence (Tray system not covered by the Guarantee of Excellence)

Each tray has an overall internal dimension of: 43.18 x 19.43 x 3.45 cm (LxWxD)

Also available without EMS Organiser and Dividers

[Also available with without EMS Organizer and Dividers](#)



Black Orange

1460EMS Case SPECIFICATIONS

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
52.9 x 32.3 x 32.4 cm (21" x 13" x 13")		47.1 x 25.2 x 27.7 cm (19" x 10" x 11")	
Lid Depth	Bottom Depth	Total Depth	
12.5 cm (5")	15.3 cm (6.01")	27.7 cm (10.92")	
Weight w/Foam	Weight w/o Foam	Buoyancy Max.	
8.26 kg. (18.2 lbs)	0kg (lbs.)	0 kg (lbs.)	
Range Temperature			
-40 / 99° C (-40 / 210° F)			

Materials

Body	Latch	Lid O-Ring	Pins
Polypropylene	EXL	PolymerStainless Steel	
Foam	Purge Body	Purge Vent	Purge O-Ring
Polyurethane 6 pieces	ABS	3 Micron Hydrophobic Nonwoven PET	70 Shore Nitrile

Configuration

Cat. #	Description
1460EMS	1460EMS Case

1460EMS Case Accessories

Cat. #	Description
1463	Replacement O-ring

1460EMS Case Certificates

- IP66

3D Flight Cases Ltd

Phone: +44 (0) 1733 269026 • Fax: +44 (0) 1733 530535

website: www.3D-FlightCase.co.uk